



TECHNOLOGY IN MOTION

MACO RAIL-SYSTEMS

SLIDING HARDWARE



ASSEMBLY INSTRUCTIONS

HS COMFORT CLOSE / COMFORT STOP
concealed
Timber, Guide Track C

Table of contents

Important instructions	3
<hr/>	
Function	3
<hr/>	
Fittings overview	4
<hr/>	
Preparation frame - Example: scheme A and C	5
<hr/>	
Preparation sash	6
<hr/>	
Mounting sash and frame	7
<hr/>	
Reference dimension	8
<hr/>	
Completion of guide track	8
<hr/>	
Adjustment options	9
<hr/>	
Limit opening width	9
<hr/>	
Mounting cover frame piece	10
<hr/>	
Technical data	11

Important instructions

Target group


This documentation is intended exclusively for specialist companies and certified specialists. The work described herein must only be carried out by certified specialists.

Usage and safety information

In addition to this information, the profile-dependent assembly instructions for HS-Hardware System A, C, G, K Timber, Order No. 757077EN, must be complied with. In the Comfort Close assembly instructions, only the differences from the above document are described. Mount all hardware parts professionally as described in this manual and observe all safety instructions.

The HS Comfort Close may only be used in combination with gasket tracks – HS Set or Upper HS gasket track in PVC for slim cross-bars.

Function




Function Comfort Close


Shortly before reaching the main closing edge, the sash is slowed down gently and is then retracted automatically to the closed position.

Fittings overview

Pos.	Description
6.1	Guide Track
15.1	Comfort Cose
16.2	Frame piece
16.3	Cover frame piece

Note: All measurements in this document are indicated in millimetres.



required for mounting: guide track	6.1  Guide track C
---------------------------------------	---

Screws are not included in scope of delivery. Respective specifications represent a recommendation, only.


Items per sliding sash

		Article description	Item Code
1	Comfort Close 15.1 ²⁾	size 1 ≤ 200 kg sash weight ≤ 30 N sliding force	300359
		size 2 > 200 ... 300 kg sash weight ≤ 50 N sliding force	300360
1	Frame piece, adjustable	16.2	305134
1	Cover frame piece	16.3	304816


¹⁾ optional ²⁾ Colour of damper: size 1 - black, size 2 - silver-grey

Preparation frame - Example: scheme A and C


Scheme A



- A** Divide guide track (6.1):
 scheme A: handle side: FB - 90 mm, fixed sash side: FB + 8.
 scheme C: passage area: 2.FB - 188, fixed sash: FB + 8.
- B** Fasten guide track on handle side.
- C** Pre-drill 2 fastening holes Ø 4.2.
- D** Fasten frame piece (16.2).



Scheme C




*) based on 56 frame;
 in case of deviation,
 please contact
 MACO.


Preparation sash

A Carry out sash milling on non-handle side. Mill groove 6 x 4 mm for adjustment of Comfort Close.

B Comfort Close (265) has to be pretensioned. Mount the Comfort Close with 2 screws 4.5 x 25.



Mounting position




Mounting sash and frame



Attention: Risk of injury due to fallen sash! To avoid the risk of injury, perform the following steps with two workers.


A Set down the sliding sash onto the running track in the area of the fixed sash and swivel it into the element.

B Bring handle into „Open“ position and slide the sliding sash to the transit area.




Reference dimension

- › To check the height of the frame piece, swivel in the sash, lift it and slide into closing position.
- › Measure reference dimension within the range of the Comfort Close (desired value = 6 mm).
- › If necessary, push the sash to one side and adjust the frame part to compensate for the difference to the control dimension (see "Adjustment options").
- › Fasten guide track on fixed sash side.



Completion of guide track



**Example: scheme A;
scheme C accordingly**
Fasten the guide track at frame profile.


Adjustment options

In case of inaccuracy concerning position of the frame piece, the reference dimension concerning the height of the frame piece and the end position of the sash related to the frame can be adjusted.

To do this, the sash has to be opened.


- > (1) Correction of the lateral position (+/- 5 mm):
 - (1.1) Loosen screw by means of Torx 25,
 - (1.2) Slide frame piece into the desired direction:
 - 0 – 5 mm: closing of sash will be shifted in direction of handle side;
 - 0 + 5 mm: closing of sash will be shifted in direction of non-handle side
 - (1.3) Fasten screw with max. 3 Nm.
- > (2) Correction of the height of the frame piece (+ 3 mm) with Torx 15.

Adjustment at closing edge




(Sash opened)

0 – 5 mm: towards closing position (frame)
0 + 5 mm: off the closing position (frame)




Note: Adjustments may be changed after glazing the sash and mounting the frame!

Limit opening width



Mounting cover frame piece





Technical data

Range of application scheme A:

Sash width (FB)	720 – 3385 mm
FB _{min.}	885 mm
Sash height (FH)	745 – 2870 mm
Outer frame width (RAB)	6500 mm
Sash weight or sliding force without Comfort Close	size 1: max. 200 kg or max. 30 N size 2: max. 300 kg or max. 50 N (further sizes on request)


Depending on version of the profile sealing to be used, it can happen, that the sash cannot close completely.

Dimensions (W x H x D) Comfort Close	336 mm x 27.5 mm x 22 mm
Soft move-in	starting approx. 100 mm off the closing edge
Increase of sliding force with Comfort Close	size 1: by 25 N (black) size 2: by 45 N (silver-grey)

Range of application is depending on used profile systems. Specifications of profile manufacturers to be observed.

You want everything from a single source?

We provide you with complete solutions for sliding doors, windows and doors – for timber, PVC and aluminium. Experience our versatile system offer, comprehensive service included. Discover more of this on our website www.maco.eu or contact your MACO representative.



MACO near you:
www.maco.eu/contact



TECHNOLOGY IN MOTION



This print document is revised regularly.
The latest version is available at <https://www.maco.eu/assets/757757>
or by scanning the QR code.

Created: 02/2019 - Changed: 08.09.2021
Order no. 757757
All rights reserved and subject to change.