



The slide & tilt system

MACO Move SK – enhanced ease of use and security



A handle

with more quality of life

For the best indoor climate and reliable burglary protection: That's what MACO Move SK is for. Floor-to-ceiling casement doors weighing up to 200 kg can be implemented with the slide & tilt system. Whether made of uPVC, timber, timber-aluminium or aluminium. And with the certainty that the room is well ventilated and burglary protection is enhanced even when in the tilted position. Greater ease of use with added security: MACO Move SK, the slide & tilt system





Benefits for fabricators

01 Wide variety

Everything from a single source: Hardware solutions for slide & tilt doors made of uPVC, timber, timber-aluminium or aluminium.

02 Highly advanced modular design

Easy to combine: **MACO Move SK** offers a range of compatible hardware elements that let you implement secure and customised solutions.

03 Impressive durability

For ease of use with security: all hardware solutions with a 10-year functional warranty.

Benefits for consumers

01 Low-maintenance ease of use

Light and secure: **MACO Move SK hardware** enables effortless and infinitely variable opening, holding and closing of large sliding doors – for a long time and without requiring regular readjustment.

02 Lasting quality

Longer lasting smooth operation: Pre-assembled cleaning brushes keep the rollers clean and thus maintain ease of sliding for years.

03 Built-in security

Certified and confirmed: The slide & tilt hardware offers enhanced burglary protection – even when the sliding element is in the vented position.





Product variants

MACO Move SK Z

Automatic opening and closing function: With the hardware solution with positive control, operation using a handle lever is safe and effortless – with casement doors weighing up to 200 kg.

MACO Move SK PAS

MACO Move SK PAS enables implementation of sliding doors weighing up to 200 kg. The unique feature is the integrated spring mechanism which automatically pulls the window sash towards the frame when closing. Hardly any tension or compressive force needs to be exerted on the sash.

MACO Move SK Upgrade

Quieter and more stable: hardware for noticeably greater ease of use when sliding, tilting and closing floor-to-ceiling sliding doors with a sash weight of up to 200 kg.

MACO Move SK SE

For maximum operating safety: The self-engaging hardware solution ensures that the window sash is always fixed in the correct position – extending the service life of the entire construction.

MACO Move SK S

For sliding doors with manual opening and closing function and a 160 kg sash weight. The fixed door frame clearance of 35 mm eliminates the need for cost-intensive double profiles.



Special features

MACO i.S. security roller cam

High burglary protection even in the vented position – as a standard feature. This is ensured in all **MACO Move SK** hardware solutions by the **MACO i. S. security roller cam** with its special design. At the same time, it also optimises the contact pressure of the sash against the frame and automatically compensates for tolerances in the rebate clearance. The effect: a better indoor climate.

Tricoat - Evo

All **MACO Move SK** sash hardware solutions are available with the **Tricoat-Evo** option. This four-layer surface finish is three times harder than steel and features impressive corrosion protection and abrasion resistance. This means that the hardware can withstand daily wear and tear for even longer and combine ease of use with security.



More solutions:

) Handles

Information, solutions, advice

MACO is here for you

Find out more about MACO Move slide & tilt hardware at www.maco.eu/movesk and download additional documentation, installation instructions and certificates. You can also find the MACO customer consultant in your area by visiting our website. Contact us for personalised advice – we look forward to helping you.

MACO near you: www.maco.eu/contact

